



# Ledinaire Waterproof

## WT060C LED56S/840 PSU TW1 L1500 BN

Ledinaire Waterproof, 46 W, L1500 mm, 5600 lm, 4000 K, Symmetrical, Opal, IP66, IK08, TW1

The Ledinaire waterproof (WT060) range contains a selection of popular off-the-shelf waterproof LED luminaires that comes with the high Philips quality levels at a competitive price. Reliable, energy efficient and affordable. Ledinaire enables, simple and quick installation, with optional through wiring possibility.

### Product data


General Information			
Light source replaceable	No	Luminous Efficacy (rated) (Nom)	120 lm/W
Number of gear units	1 unit	Color rendering index (CRI)	>80
Driver included	Yes	Flickering value (PstLM)	1
Feed-through wiring	Feed-through wiring 1-phase	Stroboscopic effect value (SVM)	1.6
Service tag	No	Beam angle of light source	120 degree(s)
Lighting Technology	LED	Light source color	840 neutral white
Value ladder	Value	Optic type	Symmetrical
CE mark	CE mark	Luminaire light beam spread	120°
Warranty period	3 years	Unified glare rating CEN	26
Flammability mark	For mounting on normally flammable surfaces	Operating and Electrical	
ENEC mark	-	Input Voltage	220 to 240 V
Glow-wire test	Temperature 850 °C, duration 30 s	Line Frequency	50 or 60 Hz
EU RoHS compliant	Yes	Inrush current	3.3 A
Light Technical		Inrush time	0.115 ms
Luminous Flux	5,600 lm	Power Consumption	46 W
Correlated Color Temperature (Nom)	4000 K	Power Factor (Fraction)	0.9
		Connection	Connection unit 3-pole
		Cable	-

Ledinaire Waterproof

Number of products on MCB of 16 A type B	10
Temperature	
Ambient temperature range	-20 to +45 °C
Controls and Dimming	
Dimmable	No
Driver/power unit/transformer	Power supply unit (On/Off)
Constant light output	No
Mechanical and Housing	
Housing Material	Polycarbonate
Reflector material	Polycarbonate
Optic material	Polycarbonate
Optical cover material	Polycarbonate
Fixation material	Stainless steel
Housing Color	Grey
Optical cover finish	Opal
Overall length	1,558 mm
Overall width	69 mm
Overall height	59 mm
Dimensions (Height x Width x Depth)	59 x 69 x 1558 mm
Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Sustainability rating	-
Protection class IEC	Safety class II
Photobiological risk	Photobiological risk group 0 @200mm to EN62778

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Initial chromaticity	<5
Power consumption tolerance	+/-10%
Over Time Performance (IEC Compliant)	
Control gear failure rate at median useful life 50000 h	7.5 %
Lumen maintenance at median useful life* 50000 h	75
Lumen maintenance at median useful life* 75000 h	70
Application Conditions	
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Suitable for random switching	Yes
Product Data	
Order product name	WT060C LED56S/840 PSU TW1 L1500 BN
Full product name	WT060C LED56S/840 PSU TW1 L1500 BN
Full product code	871016336012699
Order code	911401876980
Material Nr. (12NC)	911401876980
Numerator - Quantity Per Pack	1
EAN/UPC - Product/Case	8710163360126
Numerator - Packs per outer box	12
EAN/UPC - Case	8710163360249

Dimensional drawing



## Ledinaire Waterproof

